

## Smooth Cotton Pearlescent

### GSCPJ

ILFORD GALERIE Smooth Cotton Pearlescent is a mould made 100% Cotton Rag paper with a “ultra smooth” surface, featuring a unique “Pearlescent” finish. ILFORD’s new original coating technology adds another dimension to the cotton range, with a stunning sparkle effect. Photographers, artists and print-makers can now create brilliant inkjet prints with an ultra smooth surface and shimmer.

#### FEATURES

- Ultra Smooth surface
- 100% Cotton rag base
- Mould made paper
- Pearlescent finish
- Original “Sparkle” effect coating technology

#### Note;

Due to the unique coating characteristics of this paper (shimmer/sparkle effect) it may be necessary to increase image density 10% to 20% using tone curve adjustments.  
Further adjustments may also be required for color matching.

#### PRINTER & INK COMPATIBILITY

Designed for use with both desktop and wide format inkjet printer system using either aqueous dye or pigment inks from major manufacturers.

#### PHYSICAL PROPERTIES

Weight	310gsm
Opacity	> 98%
Caliper	550 Micron
Tint	97,5   0,3   1,8
OBA Content	No
Acid Free	Yes

#### HANDLING TIPS

Finished prints should be interleaved and stored carefully to prevent scratching. FineArt paper prints are typically more delicate than conventional resin coated (RC) papers such as Pearl, Glossy, Lustre surfaces and should be handled with additional care. Before printing please check that there are no loose paper fibres or debris on the media surface as this may lead to print errors. As with any FineArt media using raw paper it is possible that some debris may exist.

ILFORD have taken great care to ensure that in general our papers are free from loose paper fibres, but please check before you make the final print. Cotton gloves are recommended to avoid contaminants getting onto the surface.

#### STORAGE

It is recommended that you store your paper in the original product packaging/boxes. Products must be stored in a cool, dry environment away from direct sunlight. Optimal storage and Operating conditions are 15-25°C, 35-65% relative humidity, non-condensing.

#### AVAILABILITY

Available in sheets. For more details please see the product page on [www.ilford.com](http://www.ilford.com).